

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106 1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

## **TEST REPORT**

Client :	Basford Brands Pty Ltd	Test Number	:	16-005101
	18-20 Apparel Close	Issue Date	:	23/09/2022
	Breakwater VIC 3219	Print Date	:	23/09/2022

Sample Description	Clients Ref : "Libretto" Sheer woven fabric
	Colour : Shadow (Grey) End Use : Curtains
	Nominal Composition : 100% Polyester Nominal Mass per Unit Area/Density : 89g/m2

AS 1530.2-1993

## Methods for Fire Tests on Building Materials, Components and Structures. Part 2: Test for Flammability of Materials

Date Tested			23/09/2022	
Flammability Index			1	
		Length	Width	
Spread Factor		0	0	
Heat Factor		1	1	
Maximum height (d)				
Mean		1.0	1.0	
Coefficient of Variation		0.0	0.0	%
Heat (a)				
Mean		1.5	1.5	°C.min
Coefficient of Variation		0.0	0.0	%
Number of Specimens		6	6	
Tested				
Observation	Melting			

These test results relate only to the behaviour of the test specimens of the material under the particular conditions of the test, and they are not intended to be the sole criterion for assessing the potential fire hazard of the material in use.



MANAGING DIRECTOR



Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106 1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

## **TEST REPORT**

Client :	Basford Brands Pty Ltd	Test Number	:	16-005102
	16 - 20 Apparel Close	Issue Date	:	29/09/2022
	Breakwater VIC 3219	Print Date	:	29/09/2022

Sample Description	Clients Ref : "Libretto"					
	Sheer woven fabric					
	Colour : Shadow (Grey) End Use : Curtains					
	Nominal Mass per Unit Area/Density :	89g/m2				
AS/NZS 1530.3-1999	Methods for Fire Tests on Building Materials, Components and Structures Part 3: Simultaneous Determination of Ignitability, Flame Propagation, Heat Release and Smoke Release					
	Face tested:	Face				
	Date tested:	29/09/2016				
		Standard Error	Mean			
	Ignition time	Nil	Nil min			
	Flame propagation time	Nil	Nil sec			

Ignition time	Nil	Nil	min
Flame propagation time	Nil	Nil	sec
Heat release integral	Nil	Nil	kJ/m²
Smoke release, log d	0.0133	-1.8807	
Optical density, d		0.0132	/ metre
Number of specimens ignited:		0	
Number of specimens tested:		6	
Regulatory Indices:			
Ignitability Index		0	Range 0-20
Spread of Flame Index		0	Range 0-10
Heat Evolved Index		0	Range 0-10
Smoke Developed Index		1	Range 0-10

72318

15099

© Australian Wool testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Chemical Testing - Mechanical Testing - Performance & Approvals Testing

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

: Accreditation No. : Accreditation No. : Accreditation No.

1.

•

983 985 1356



Page 1 of 2



APPROVED SIGNATORY

0204/11/22



Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106 1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

## TEST REPORT

Client : Basford Brands Pty Ltd 16 - 20 Apparel Close Breakwater VIC 3219

16-005102 Test Number : **Issue Date** 29/09/2022 29/09/2022 **Print Date** •

These results only apply to the specimen mounted, as described in this report. The result of this fire test may be used to directly assess fire hazard, but it should be recognised that a single test method will not provide a full assessment of fire hazard under all fire conditions.

The reaction of thin unsupported flexible materials to flame impingement can be assessed in accordance with AS 1530.2. Where materials of thickness less than 2mm that are sufficiently flexible to be bent by hand around a mandrel of 2mm diameter or less are subjected to the test described herein, they should also be subjected to the test in AS 1530.2.

Ignition is initiated by a pilot flame that is held near, but does not touch the specimen. A material that does not ignite during the standard test may ignite if contacted with a pilot flame during the test

To allow free movement of sample during testing all corners were folded away from the clamps.

Each test specimen was sandwiched between two layers of galvanised welded square mesh made from wire of nominal diameter 0.8mm and nominal spacing 12mm in both directions, stapled through at four points, each 100mm from the centre of the sample and the assembly clamped in four places.

72318 Australian Wool testing Authority Ltd Copyright - All Rights Reserved

15099



the Managing Director of AWTA Ltd

Accredited for compliance with ISO/IEC 17025 - Chemical Testing Mechanical Testing Performance & Approvals Testing

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by

: Accreditation No Accreditation No · Accreditation No

1356

983 985

Page 2 of 2







APPROVED SIGNATORY

0204/11/22

C