AWTA PRODUCT TESTING

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

TEST REPORT

Client: Basford Brands Pty Ltd

16 - 20 Apparel Close Breakwater VIC 3219 **Test Number** : 24-004333

Issue Date : 28/11/2024
Print Date : 28/11/2024

Sample Description Clients Ref: "Mizumi"

Woven fabric

Colour: Grey

End Use: Curtains

Nominal Composition:

100% Polyester

Nominal Mass per Unit Area/Density: 330g/m2

Nominal Thickness: Approx: 1mm



337145 73803 Page 1 of 3

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing Accreditation Numbers: 983, 985, and 1356

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.



MICHAEL A. JACKSON B.Sc.(Hons)

Fiona McDonald

APPROVED SIGNATORY

AWTA Product Testing

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

TEST REPORT

Client: Basford Brands Pty Ltd

> 16 - 20 Apparel Close Breakwater VIC 3219

Test Number : 24-004333 **Issue Date**

Print Date 28/11/2024

AS/NZS 1530.3-1999

Methods for Fire Tests on Building Materials, Components and Structures Part 3: Simultaneous Determination of Ignitability,

Flame Propagation, Heat Release and Smoke Release

Face tested:

Face

Nil

Standard Error

Date tested:

28-11-2024

Mean

Nil min

Nil

28/11/2024

Ignition time Flame propagation time Heat release integral

Nil Nil

Nil

kJ/m²

Smoke release, log d

0.1334

-2.3255

Optical density, d

0.0845 / metre

No of samples which ignited

1

For Samples which ignited Smoke Release (Log D) - Mean

-1.0734

Smoke Release (Log D) - Standard Error

0.0000

No of samples which did not ignite For Samples which did not ignite

Smoke Release (Log D) - Mean Smoke Release (Log D) - Standard Error

the Managing Director of AWTA Ltd.

-2.3255 0.1334

Number of specimens tested:

9

Regulatory Indices:

Ignitability Index

Range 0-20

Spread of Flame Index Heat Evolved Index

Range 0-10

Smoke Developed Index

Range 0-10

Range 0-10

Page 2 of 3

337145

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved

73803

Accredited for compliance with ISO/IEC 17025 - Testing

Accreditation Numbers: 983, 985, and 1356

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by

A. JACKSON B.Sc.(Hons) ANAGING DIRECTOR

Fiona McDonald APPROVED SIGNATORY

0204/11/06



Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

TEST REPORT

Client: Basford Brands Pty Ltd

16 - 20 Apparel Close Breakwater VIC 3219 **Test Number** : 24-004333

Issue Date : 28/11/2024
Print Date : 28/11/2024

Each test specimen was sandwiched between two layers of galvanised welded square mesh made from wire of nominal diameter 0.8mm and nominal spacing 12mm in both directions, stapled through at four points, each 100mm from the centre of the sample and the assembly clamped in four places.

To allow free movement of sample during testing all corners were folded away from the clamps.

The reaction of thin unsupported flexible materials to flame impingement can be assessed in accordance with AS 1530.2. Where materials of thickness less than 2 mm that are sufficiently flexible to be bent by hand around a mandrel of 2mm diameter or less are subjected to the test described herein, they should also be subjected to the test in AS 1530.2.

Ignition is initiated by a pilot flame that is held near, but does not touch the specimen. A material that does not ignite during the standard test may ignite if contacted with a pilot flame during the test.

The specimens melted and flowed away from the area of maximum heat during the test. Due to this phenomena it should be recognised that this test result may not be a true indication of the product's fire hazard properties.

These results only apply to the specimen mounted, as described in this report. The result of this fire test may be used to directly assess fire hazard, but it should be recognised that a single test method will not provide a full assessment of fire hazard under all fire conditions.

337145 73803 Page 3 of 3

 Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing Accreditation Numbers: 983, 985, and 1356

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.



MICHAEL A. JACKSON B.Sc.(Hons)

Fiona McDonald

APPROVED SIGNATORY